

# Waterproof ExStik® II Dissolved Oxygen Meter/Kit



## Easy to replace screw on membrane cap

For fast replacement and operation. Extension cable and weighted probe guard included with the Kit

### Features:

- Convenient kit adds versatility on measuring Dissolved Oxygen in laboratories or out in the field with a 5m (16ft) extension cable and probe weight guard for taking easy measurements in tanks or streams
- Adjustable Altitude Compensation (0-20,000ft in 1,000ft increments)
- Adjustable Salinity Compensation from 0 to 50ppt
- Memory stores up to 25 data sets with DO and Temperature reading
- DO600 meter includes DO electrode, protective sensor cap, spare membrane cap, electrolyte, four 3V CR-2032 batteries, and 1.2m (48") neckstrap. See image on right for DO600-K Kit information.



**DO600-K** — Kit includes DO600 meter, DO603 membrane kit, 5m(16ft) extension cable, weighted probe guard, and hard carrying case — \$125 savings



Sample testing with extension cable attached to meter



Sample testing with the meter in a laboratory environment



Choice of optional 1m(3ft) or 5m (16ft) extension cable with probe weight



Extension cable attached to meter



Bonded membrane cap for easy replacement



**DO603** Membrane Kit includes 6 screw on membrane caps, 15mL filling solution and polishing paper

### Ordering Information:

**DO600** .....ExStik® II Dissolved Oxygen Meter  
**DO600-K** .....ExStik® II Dissolved Oxygen Kit  
**DO603** .....Membrane Kit for DO600 and DO605  
**DO605** .....Spare ExStik® II Dissolved Oxygen Electrode module  
**EX010** .....Extension Cable, 3ft (1 Meter) with probe weight for ExStik  
**EX050** .....Extension Cable, 16ft (5 Meter) with probe weight for ExStik

Specifications	Range	Max Resolution	Basic Accuracy
DO (saturation mode)	0 to 200.0%	0.1%	±2% FS
DO (concentration mode)	0 to 20.00ppm (mg/L)	0.01ppm (mg/L)	0.4ppm (mg/L)
Temperature	0 to 50°C (32 to 122°F)	0.1°C/°F	1°C (±1.8°F)
Dimensions	36x176x41mm (1.4x6.9x1.6")		
Weight	110g (3.8oz)		